

JLM Ceramic Engine Protector

The JLM Ceramic Engine Protector oil additive is a specialized product designed to enhance the lubrication and protection of a car's engine. It contains ceramic nanoparticles that form a durable and heat-resistant coating on the engine's internal components. This coating helps to reduce friction and wear, leading to improved fuel efficiency and potentially extended engine life. Additionally, the Ceramic Engine Protector additive can provide a higher level of protection during start-up and high-stress conditions, contributing to smoother operation and reduced engine noise.

Benefits

- Significantly reduces friction and wear
- Reduces fuel and oil consumption
- Restores engine power
- Provides long term protection of your engine
- Improves load carrying capacity of the lube film
- Reduces emission of hazardous exhaust gases
- Improves viscosity of the oil
- Provides emergency lubrication
- Reduces engine noise level
- Reduces oil temperature
- Improves cold start performance
- Prolongs engine lifetime

How to use:

For all gasoline, diesel and LPG engines with or without turbochargers. Can be mixed with all commercially available engine oils. Does not clog filters and is not harmful for catalytic converters. Not suitable for motorcycles using a wet clutch.

Shake well before use. Add contents of one bottle to the warm motor oil, preferably shortly after oil change. Drive approximately 15 minutes to obtain optimum result. Make sure the oil contents do not exceed the maximum oil level in your engine.

One bottle treats 4 to 6 litres of motor oil.
Recommended use: every 50.000 km



SCAN FOR MORE INFO:



	J06065 JLM Ceramic Engine Protector	J06050 JLM Bortec Oil Additive		
	MoS2	Teflon	Ceramic	Bortec
Compound	Molybdenum Disulphide	PTFE	Boron Nitride	Boron Nitride (dissolved)
Color	Black/Grey	Cream White	(Cream) White	Honey
Friction coefficient	~ 0,7	~ 0,6	< 0,2	< 0,2
Thermal stability	Medium	Low	High	High
Particle size	~ 1-3 µ	< 0,5 µ	~ 0,25µ	n/a
Application	> 5 years	> 5 years	> 2 years	> new cars



WE UNDERSTAND CARS

jlm Lubricants.com

Product information

Art. Nr: J06065

Barcode: 8718274351835

HS code : 27101999

Ufi Code : YQSH-90NT-Q00H-M7QW

Pack Size : 250ml

Quantity in box: 12

Weight full box: 350 gram

Boiling point: No data available

Density at 20 °C: 0.891 g/cm³

Flash point: > 201 °C

Colour: White

Odour: Characteristic

J06065-EN-V1

The information in this sheet is correct and true to the best of our knowledge, but any recommendations or suggestions made in this sheet are made without guarantee since the conditions of use are beyond our control. We do not accept responsibility for damage because of incompleteness, negligence and/or inaccuracies in this information sheet. The above typical values do not constitute a specification nor does the information in this sheet imply any legally binding assurance of certain properties or of suitability for a specific purpose.